

Travertino Beige Bocciardato

— HADO



AMBIENCE

1000x3000 mm / 39.4"x118.1"

3 Available Faces Supplied Randomly

3 Facce fornite in modo "random" | 3 Disponible en faces fournies aléatoirement |

Dekor mit 3 möglichen Verläufen Musterverlauf nach Zufallsprinzip | 3 Caras disponibles de manera aleatoria.



1000x3000 mm

Laminam 5

Coefficient of friction: Laminam 5 / Laminam 5+

Coefficiente d'attrito | Coefficient de frottement | Reibungskoeffizient | Coeficiente de fricción |

Norm-Method <i>Norma-Metodo Norme-Méthode Norm-Methode Norma-Metodo</i>	1000x3000 mm
EN 16165* - Annex B	R10
ANSI A137.1 (DCOF)*	≥ 0,42

Pendulum

Norm-Method <i>Norma-Metodo Norme-Méthode Norm-Methode Norma-Metodo</i>		
Spanish test*	UNE-ENV 12633:2003	on demand
English test*	BS 7976-2:2002 PENDULUM Test	on demand
Australian test*	AS/NZS 4586	on demand

* Guaranteed if requested at the time of ordering | *Garantito su richiesta in fase d'ordine |*

Garanti sur demande au moment de la commande | auf Anfrage in der Bestellphase garantiert | Garantizado por encargo durante la fase de pedido

Pictures colours and features have to be considered indicative. If tones or characteristics of the images are not considered indicative. | Les teintes et les caractéristiques des images sont uniquement à titre indicatif | Die gezeigten Farben und Muster sind zurällig und nicht verbindlich | Los tonos y los característicos de las imágenes deben considerarse solamente indicativos